



MODELS

- PFLO1524-1/2
- PFLO2025-1
- PFLO2025-8PK
- PFLO1/2-ROLL25
- PFLO1/2-ROLL48
- PFLO1-ROLL25
- PFLO1-ROLL30
- PFLO1-ROLL48
- PFLO1-ROLL72



**FEATURES**

A unique alternative to hogs hair. Available in 15"x24" or 20"x25" pre-cut pads or rolls. Rigid construction needs no frame. Cleans easily with water, fibers unaffected by moisture. Safe to handle, no fiberglass, sharp edges, flaking or shedding. Bi-directional air flow. Can be easily cut-to-fit with scissors.

**PRODUCT DETAILS**

- Blue self-supporting rigid polyester fiber w/proprietary binder
- UL Classified as to Flammability Only
- Self Extinguishing -- FMVSS 302 Certified
- Available in 1/2" or 1" nominal thickness
- Product Weight: 1/2": 22.5 +/- 2.0 ounces per Square Yard; 1": 24.3 +/- 2.0
- Maximum operating temperature 200°F (use at 200°F can cause softening, prolonged use can cause media to become brittle)
- Initial air flow resistance - 1/2" 0.03 in. w.g.@1200 cfm; 1": 0.07 in. w.g.@1200 cfm
- Arrestance efficiency - 1/2": 70%; 1": 80%
- Dust Holding Capacity - 1/2": 316 grams; 1": 343 grams

Roll Sizes:

- 25" x 48' x 1/2"
- 48" x 48' x 1/2"
- 25" x 36' x 1"
- 30" x 36' x 1"
- 48" x 36' x 1"
- 72" x 36' x 1"